


Pluggable Interface Relays and Bases

CR-M Range (without LED's)



Part Number	Control Voltage	Number of Contacts	Contact Rating	Description	Order Code	ZAR Price
CR-M012DC2	12VDC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R4000	R100
CR-M024DC2	24VDC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R1000	R100
CR-M230AC2	230VAC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405611R3000	R117
CR-M012DC4	12VDC	4 c/o (SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R4000	R106
CR-M024DC4	24VDC	4 c/o (SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R1000	R106
CR-M230AC4	230VAC	4 c/o (SPDT)	6A @ 250V	14 Pin Pluggable Relay	1SVR405613R3000	R124

Notes Relays has a test flag function which can be latched. The flag is Green for DC or Orange for AC coils. Relay Bases are DIN 35 Rail Mounted. C/O can be paralleled to increase the Current Rating. Choose the CR-U Range if higher current rating is required.



Base for CR-M Relays

CR-M2SS

Standard Base for CR-M 2 c/o Relay 1SVR405651R1000 R62

CR-M4SS

Standard Base for CR-M 4 c/o Relay 1SVR405651R3000 R72

Pluggable Interface Relays and Bases

CR-U Range (without LED's)



Part Number	Control Voltage	Number of Contacts	Contact Rating	Description	Order Code	ZAR Price
CR-U012DC2	12VDC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R4000	R150
CR-U024DC2	24VDC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R1000	R150
CR-U230AC2	230VAC	2 c/o (SPDT)	12A @ 250V	8 Pin Pluggable Relay	1SVR405621R3000	R159
CR-U012DC3	12VDC	3 c/o (SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R4000	R155
CR-U024DC3	24VDC	3 c/o (SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R1000	R155
CR-U230AC3	230VAC	3 c/o (SPDT)	10A @ 250V	11 Pin Pluggable Relay	1SVR405622R3000	R165

Notes Relays has a test flag function which can be latched. The flag is Green for DC or Orange for AC coils. Relay Bases are DIN 35 Rail Mounted. C/O can be paralleled to increase the Current Rating. Choose the CR-M Range if space is a consideration.



Base for CR-U Relays

CR-U2S

Standard Base for CR-U 2 c/o Relay 1SVR405670R0000 R75

CR-U3S

Standard Base for CR-U 3 c/o Relay 1SVR405660R0000 R77

Notes:

* More options on the relays are available on request, ie; CR-M/CR-U with LED and non standard coil voltages.

* For accessories on the relays please enquire with us, ie; diode, varistor etc.

* For CR-M type, see page 277 in the 2017-2018 ABB Price Catalogue.

* For CR-U type, see page 281 in the 2017-2018 ABB Price Catalogue.

* For CR-M socket/base, see page 279 in the 2017-2018 ABB Price Catalogue.

* For accessories, see page 282 in the 2017-2018 ABB Price Catalogue.